

# TECHNICAL DATA SHEET



## PARA 88



Para 88 reflector



Para 88 kit

Article number	33.482.00	33.483.00
Allowed max. energy	3200 J	3200 J
f-stop at 2 m (6 ½ ft) distance	focused: f: 90 defocused: f: 64	focused: f: 64 9/10
f-stop at 10 m (33 ft) distance	focused: f: 22 defocused: f: 11	focused: f: 22 8/10
Inside coating	silver	silver
Dimensions (without stand)	open: 85 x 64 cm (34 x 24")  closed: 20 x 83 cm (8 x 33")	open with focusing system: 85 x 107 cm (33 x 42") closed with focusing system: 32 x 107 cm (13 x 42")
Weight	2.8 kg (6.2 lbs), without case	5.5 kg (12.1 lbs), without case
Compatibility	Litos Unilite Pulso G Pulso-Twin Pulso 8 Picolite / Mobilite 2 lamp with Pulso adapter Ringflash P broncolor HMI F575.800	Litos Unilite Pulso G Pulso-Twin Pulso 8 Picolite / Mobilite 2 lamp with Pulso adapter Ringflash P broncolor HMI F200 * broncolor HMI F400 * broncolor HMI F575.800 *) in combination with 33.489.01
Accessories	Diffuser (low degree): 33.472.00 Diffuser (mid degree): 33.472.00 Diffuser (high degree): 33.472.00 Light grid 40°: 33.221.00 Adapter P: 33.489.00 Adapter D: 33.489.01 Modification kit Ringflash for Para 88: 36.140.00 Adapter Ringflash P for Para 88: 33.489.04 Ringflash P for Para 88: 32.463.XX Focusing system P: 33.488.00 Focusing system D: 33.488.01	Diffuser (low degree): 33.472.00 Diffuser (mid degree): 33.472.00 Diffuser (high degree): 33.472.00 Light grid 40°: 33.221.00 Adapter P: 33.489.00 Adapter D: 33.489.01