

Product designation**Striplite 60 Evolution**

Article no. 32.301.XX

Product description

Light with dimensions 58 x 12 cm / 22.8 x 4.7 inches can be operated at up to 1 x 3200 J, plexiglass diffuser, sheet steel back with cable outlet, 5 meter / 16.4 ft. cable, modelling light switch, and separate interchangeable tilt head.

Scope of delivery

Striplite with one cable, flash tubes, modelling lamps and interchangeable tilt head.

Technical data

Flash energy		1 x 3200 J
F-stop at 2 m (6 ½ ft.), 100 ISO		32 1/10
Modelling light	220 V	10 x 20 W / 24 V
	110 V	10 x 20 W / 12 V
Cable length		1 x 5 m / 16.4 ft.
Cooling		1 fan
Dimensions		58 x 12 x 13 cm / 22.8 x 4.7 x 5.1 inches
Weight		3.6 kg / 7.9 lb

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A2 plus, A4 plus, Topas A2, A4, A8 Nano 2, Mobil, Mobil A2R Primo, Primo A, Primo A fashion, Primo 4, Pulso 2, A2, 4, A4, Pulso G Opus 2, A2, 4, A4, A8,
-------------	--

For heat-related reasons, it is not possible to equip the Striplite with a proportional halogen modelling lamp matching the other lamps.

Accessories

- Art. no. 33.217.00 Honeycomb grid to Striplite 60 Evolution
- Art. no. 33.228.00 Barn door to Lightbar/Striplite 60 Evolution
- Art. no. 33.272.00 Plexi cap mat to Lightbar 60 Evolution
- Art. no. 33.274.00 Striplite attachment for Lightbar 60 Evolution

Application / arguments

Mirror projection of lines, sharp edges and contours - Separation of the dark background from shiny and not shiny objects - Background gradations - The slim built product allows a precise light control - The possibility of transforming a Striplite into a Lightbar increases the application range - Simple and versatile mounting with the interchangeable tilt head.